



ZM-A310 Chipping spreader



Hangzhou IKOM Machinery Co.,Ltd







Specification:

Mode	ZM-A310	
Specification		
1	Dimension	2500×2000×1900 (mm)
2	Chipping Size	5~20 (mm)
3	Spreading Width	MAX 3100 (mm)
4	Total Weight	1050 (Kg)
5	Shipping Dimension	2650×2150×2050 (For reference)
Main Fitting		
1	Hydraulic drive system	
2	OMR-80 Hydraulic Motor	
3	CBN-E3 Hydraulic gear Pump	
4	VFc001-2025Lr/c Preference Diverter Valve	
5	"Open" Pneumatic Cylinder	
6	GX270 Gasoline Engine	
7	One position switch	

Chassis requirements:

Dump truck Hopper width: 2410-2460 mm

Height from hopper floor to ground≥1350mm

Introduction:



HONDA GX270 Generator Power Unit



Hydraulic Driven spread roll



Control Panel



Spread Roll



13 pnuematic valve for adjusting the width



Hand wheel for adjusting the thickness

Pictures:



Factory Profile











IKOM Construction Machinery, China **Top 3 asphalt truck brand**, located in Hangzhou, it is the subsidiary company of ZHUMA Construction Machinery Group, The ZHUMA passed the ISO9001:2000 international quality system certification and products 3C authentication, the products cover Chip sealer, Slurry sealer, Concrete paver, Asphalt finisher, Chipping spreader, Bitumen decanter, emulsion plant and 50 various models, and gradually realize the product standardization and serialization and industrialization.

Our engineer team has 20 years experiences focused on Asphalt machinery technology, and our brand **footprints travel across 55 countries.** IKOM is committed to offering high quality, reliable products and service on time. Your satisfaction is our commitment. Let us be your trusted partner.

Certificates:





















